

LX

ECOBULK LX Composite

Featuring new
plastic-composite pallet.



New plastic-composite pallet:

- Improved handling properties
- Improved stability and robustness
- Significantly reduced variation of tara weight
- Best suitability for conveyor belts, high rack warehousing and shipping in ISO-containers
- Weatherproof and mildew-proof
- Easy and efficient stacking for best storage room utilisation
- Significant reduction of active staining by abrasion, splints or debris
- Improved reuse capability
- Environmentally friendly

SCHÜTZ INDUSTRIAL PACKAGING

The Future's Technology. Today.



MATERIAL

Inner bottle

- Extrusion blow-moulded HDPE
- SMP protective barrier (optional)

Outer container

- Welded tubular steel grid, galvanized

PALLETS (4-way entry)



CERTIFICATIONS

UN 31 HA1/Y (optional)

- Maximum density 1.6

FDA (optional)

- Safe for food products

CAPACITY

LX 1000

- 1,000 litres (275 gal)

FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap

OUTLET VALVES


- Integrated butterfly valve DN 50

DIMENSIONS

- 1,200 x 1,000 x 1,160 (L x W x H)

DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods



WEIGHT

LX 1000

- With plastic-composite pallet 63 kg

STATIC LOAD

Max.
3-high

