

SX-EX

ECOBULK SX-EX

If the atmosphere turns explosive, you'll need a container that is safe.



- Suitable for utilisation on explosive endangered operation premises classified as zone 1 and zone 2 (while complying with statutory and company-specific safety precautions and regulations)
- Increased resistance against mechanical and thermal stress
- Electrostatically safe within the context of the Cenelec Report CENELEC TR50404 (2003) and TRBS 2153
- Steel sheet jacket protects the container from electrostatic charge

Please do not hesitate to contact us regarding any technical concerns or questions.

SCHÜTZ
INDUSTRIAL PACKAGING

The Future's Technology. Today.



MATERIAL

Inner bottle

- Extrusion blow-moulded HDPE
- SMP protective barrier (optional)
- Additional UV and light protection of the filling product (optional)


Outer container

- Welded tubular steel grid, with steel case

Bottom plate

- Made of steel plate to provide stability and to facilitate minimum residual contents from the inner container
- Galvanized

PALLETS (4-way entry)



CERTIFICATIONS

UN 31 HA1/Y (optional)

- Maximum density 1.6
- Tested for electrostatic safety
- Suitable for use in ex-zones 1 & 2



IIA



IIB

(optional)

FDA (optional)

- Safe for food products

CAPACITY

SX-EX 1000

- 1,000 litres (275 gal)

OUTLET VALVES

- Earthed integrated butterfly valve DN 50
- Earthed screwable butterfly valve DN 50
- Earthed screwable butterfly valve DN 80


FILLING OPENING

- DN 150 with screw cap
- DN 225 with screw cap

DYNAMIC LOAD

Filled ECOBULK according to the specific weight of the filling goods

up to 1.5 2-high
more than 1.5 1-high



DIMENSIONS

- 1,200 x 1,000 x 1,160 (L x W x H)

WEIGHT

SX-EX 1000

- 75 kg with steel pallet

STATIC LOAD

Max.
4-high

